A 1321 Advanced PCIe Card

PCIe Bus Two Port Card Support Ground Isolated RS422 / RS485 selectable



- ★RS422/RS485 easy to set by DIP Switch
- ★Support ADDC feature in RS485.
- **★**Suitable for industrial control
- **★**Suitable for Windows 2000/XP
- ★Suitable for Vista & WIN7
- **★**Suitable for Linux

${ m A132I}$ Specification:

Serial Communication Controller:

*type: Moschip MCS9922.

System I/O & IRQ mapping:

- *I/O mapping assigned by PCI BIOS.
- *Memory mapping assigned by PCI BIOS.
- *IRQ mapping assigned by PCI BIOS.

Hardware compatibility:

*PCIe bus slot.

Port capability:

- *number of port: 2 ports per card.
- *Interface : Ground Isolated RS422/RS485.

Note: Each serial port can set to RS422 or RS485 by DIP switch.

- *Baud Rate: each port can be configured to 50--115200bps.
- *Connector type: DB9 male connector.

Software compatibility:

- * Windows 2000/XP.
- * Windows Vista.
- * WIN7.
- * Linux.
- * Other operation system.

Dimension:

- *A132I card: 100 * 97 mm.
- *A132I model with standard PCIe bracket.

Environment:

*operating temperature : 0°C to 55°C

*operating humidity : 10% to 95% RH

*storage temperature : 0° C to 65° C

*storage humidity: 5% to 95% RH

Performance upgrade capability and relative products:

*A102 : PCIe card support two RS232 ports.

*A112: PCIe card support two RS232/RS422/RS485 ports.

*A102: PCIe card support two RS232 ports.

*A104 : PCIe card support four RS232 ports.

*A134: PCIe card support four RS422/RS485 ports.

*A114 : PCIe card support four RS232/RS422/RS485 ports.

*A168: PCIe card support eight RS232 ports.

***All names are the trademarks of their respective organization.

RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net

WEB: http://www.computex.com.tw/rayon

WEB: http://www.rayontech.com