PCI Four Port Card

Flexible 5V power supply only PCI card RS232/RS422 / RS485 selectable



- Suitable for Windows NT
- Suitable for WIN95/98/Me
- Suitable for WIN2000/XP
- Suitable for WIN7/8/10

- Suitable for DOS Power User
- Suitable for Linux System
- Suitable for UNIX Workgroup
- ◆ Just use 5V power supply for RS232, RS422 & RS485 serial port.
- ◆ Each serial port can set to RS232, RS422 or RS485 independently.
- ◆ Support Auto-Data-Direction-Control feature in RS485.

P5914 Specification

System Structure:

▲intelligent PCIPORT Card.

▲ external cable with four standard DB25/DB9 connector.

Serial Communication Controller:

▲type: 16550A compatible with PGA support.

▲speed: 1.8432MHz.

Software Compatibility:

▲DOS Library

▲WIN7/8/10

▲WIN2000/XP

▲ WIN95/98/Me

▲ Windows NT

▲Linux

▲SCO OpenServer

System I/O & IRQ mapping:

▲six 8byte I/O mapping assigned by PCI BIOS.

▲one IRQ mapping assigned by PCI BIOS.

Port capability:

▲Number of port: 4 ports per card.

▲Interface: RS232,RS422 or RS485 selectable independently.

▲Baud Rate:

each port can be configured to $50\sim115200$ bps.

▲Connector type:

DB25 male connector. (with A400 cable) DB9 male connector. (with P485 cable)

Hardware Compatibility:

▲5V PCI bus slot.

Dimension:

▲P5914 card: 12.0 * 10.0 cm.

Environment:

 \triangle operating temperature : 0°C to 55°C.

▲operating humidity: 10% to 95% RH.

▲storage temperature : 0°C to 65°C.

▲storage humidity: 5% to 95% RH.

☆Accessories:

TB485: DB9 Female to RS485 terminal block kit.



☆Other relative 5V power supply only eight port card product line:

Model	RS232	RS422	RS485
P5984	4	0	0
P5984P	4	0	0
P5985	0	4	4
P5914	4	4	4



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065 E-Mail: rayon@ms1.hinet.net; info@rayontech.com.tw

WEB: http://www.computex.com.tw/rayon

WEB: http://www.rayontech.com.tw