


S232io Serial Port Sharer

- ◆ One Master to Three Slave port
- ◆ Support double isolated RS232 port
- ◆ Powerful and Flexible



- ★ Any data from port A will be sent to port B,C,D simultaneously.
- ★ Any data from port B,C,D will be sent to port A only.
- ★ Support ground isolated feature between external device and S232io box.
- ★ Support double ground isolated feature between any external devices.

S232io Specification :

Serial Port interface:

- *Connector type: DB9 male connector.
- *interface type: isolated RS232.
- *Number of ports: 4 (port A,B,C,D)

Power input:

- *UP110/UP220 US/EU type power adaptor
- *100--240 VAC input.
- *5VDC 1000mA output.
- *Current consumption: 400mA @ 5VDC.

LED indicator:

- *PWR: DC power input ON indicator.
- *ATRX: serial port A TXD/RXD signal activity.
- *BTRX: serial port B TXD/RXD signal activity.
- *CTRX: serial port C TXD/RXD signal activity.
- *DTRX: serial port D TXD/RXD signal activity.

Dimension :

- *S232io box: 90mm (W) * 150mm (L) * 27mm(H)

Environment :

- *operating temperature: 0°C to 55°C.
- *operating humidity: 10% to 95% RH.
- *storage temperature: 0°C to 65°C.
- *storage humidity: 5% to 95% RH.

Other series product:

S432io box is ISO RS422/485 master port and 3 ISO RS232 slave ports.

S434io box is ISO RS422/485 master port and 3 ISO RS422/485 slave ports.

S234io box is ISO RS232 master port and 3 ISO RS422/485 slave ports.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@ms1.hinet.net

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>